

TIG

ewm[®]
WE ARE WELDING

PICOTIG 220 PULS DC

THE POWERHOUSE FOR ALL
THINGS TIG WELDING



THE PICOTIG 220 PULS DC.

Sophisticated solutions combined in a single powerful machine. The Picotig 220 puls scores across the board with features such as an integrated storage compartment for wear parts in the handle and a practical cable holder to make your work much more convenient. What's more, this powerhouse saves both electricity and money thanks to its increased efficiency and standby function. The protective cap provided as standard effectively protects the control against splash water, dirt and impacts. All this makes the Picotig 220 puls the perfect machine for use in the workshop and on the construction site.



THE BENEFITS FOR YOU +

- Lightweight, portable and compact
- Thanks to in-built Power Factor Correction (PFC), your Picotig 220 puls enables more efficient current consumption from the mains network and therefore greater power output
- High mains voltage tolerances enable uninterrupted welding, even on weak mains networks, with long mains leads and when using a generator
- Easy operation thanks to the Comfort 3.0 mini-control
- 5-pole, digital welding torch connection allows users to connect Retox XQ welding torches with X technology

3.5 m

LONG MAINS CONNECTION CABLE
WITH SHOCK-PROOF PLUG
FOR SINGLE-PHASE 230 V MAINS.

-40%
TO
+15%

Mains voltage
tolerance at 230 V

APPROX. **97 V**

VERY HIGH VOLTAGE RESERVE
FOR WELDING
CELLULOSE ELECTRODES

2

**A VARIETY OF PULSE
VERSIONS ARE AVAILABLE:**

- Average value pulsing – TIG and MMA
- Automatic pulsing – TIG

10 kg

LIGHTWEIGHT
POWERHOUSE

3-YEAR WARRANTY*

- No restriction on the number of operating hours – even when used in 3-shift operation, 24 hours a day, 7 days a week
- 3-year warranty on welding machines and 5-year warranty on transformers and rectifiers

*In accordance with the warranty conditions at www.ewm-group.com

THE CASING.

REIMAGINED, DOWN TO THE SMALLEST DETAIL.

Wherever your welding tasks may lead you, the Picotig 220 puls is the perfect companion and a true powerhouse. Its rugged casing stands up to even the biggest challenges and offers you a wide variety of different options for expansion thanks to a host of accessories. This enables you to individually adapt your Picotig to your requirements so it does just what you need it to.



CABLE HOLDER +

You can conveniently wind up the mains cable on the cable holder of the handle.



CONNECTIONS +

A foot-operated remote control can be connected as standard. All connections are protected by the casing.



MAINS CONNECTION + CABLE

The 3.5 m-long mains connection cable gives you a larger working radius.





CARRYING HANDLE +

With a storage compartment integrated into the handle, you can always have wear parts directly on hand. The sturdy, ergonomic carrying handle is installed directly ex works.



PROTECTIVE CAP +

It effectively protects the control against splash water, dirt and impacts.



FLEXIBLE CONNECTION +

The standard 5-pole torch connection is now compatible with EWM X technology. This allows you to connect digital EWM multi-function torches with display and remote-control functions, in addition to conventional welding torches.







THE WELDING PROCESSES.

THIS IS WHAT YOUR PICOTIG 220 PULS CAN DO.

How can you achieve optimal welding results? At EWM, we are always pondering this question. But what's our answer? The Picotig 220 puls. It offers maximum operating convenience, impresses with its long service life and makes all the pulse, standard and innovative welding processes available in an optimised way. Whether you're working on low- or high-alloy steel, perfect weld seams are pre-programmed.



TIG	MMA
TIG standard DC	MMA standard
Average value pulsing	Average value pulsing
Automatic pulsing	Cellulose electrodes
HF start	Antistick
Lift arc	Arcforce
spotArc®	Hot start
spotmatic	

 <p>Standard DC Perfect TIG welding with ignition parameters adapted to the power output.</p>	 <p>spotmatic Reproducible welding of uniform tack points.</p>
 <p>HF start Prevents tungsten inclusions through non-contact arc ignition.</p>	 <p>Pulsed TIG DC welding Decreases heat input, which in turn reduces distortion and discolouration.</p>
 <p>Lift arc Easy ignition of the arc without HF by pulling up the welding torch electrode after touching the workpiece.</p>	 <p>Average value pulsing Allows the user to implement, for example, WPS requirements extremely easily, even in pulsed mode.</p>
 <p>spotArc® Minimises the time required for tacking and spot welding thanks to individual triggering of the tack points with the torch trigger.</p>	 <p>Automatic pulsing To increase arc stability and penetration characteristics at low currents, the current is pulsed automatically.</p>

THE CONTROL.

EASY HANDLING: THE COMFORT 3.0 MINI.

The Comfort 3.0 mini offers you a host of innovations, making your work easy as can be – even while wearing a welding helmet and carrying out complex welding tasks.

PICOTIG 220 PULS



- Two large, easy-to-read 7-segment displays
- Click wheel for convenient use with welder's gloves
- Reliable push-button operation
- Direct access to all main functions
- All parameters at a glance
- Complete TIG sequence
- Access block to protect against unauthorised or accidental adjustment



QR CODE PROVIDES INFORMATION QUICKLY

All important information, operating instructions, accessories and other options for retrofitting can be accessed quickly in digital form using the QR code on top of the control.

WELDING TORCHES.

VERSATILITY FOR EVERY APPLICATION

With their optimised weight and ergonomic design, gas-cooled EWM welding torches are comfortable to hold and thus ensure fatigue-free work. Extreme robustness and durability also reduce wear and spare-parts costs. Whatever your needs, you can find the perfect solution in the extensive range of EWM welding torches.



TIG RETOX XQ WELDING TORCH +

- Your TIG Retox XQ welding torch is fitted with two torch triggers. This allows you to reduce the current to a secondary current during welding simply by tapping.
- It's also possible to continuously increase (up function) or reduce (down function) the current during welding.
- Welding current display.
- Grip handle ensures secure handling.
- Standard or high-flex leather hose package (HFL – with the first metre after the handle coated with highly durable, yet soft, nappa leather).

FLEXIBLE CONNECTION +

- The standard 5-pole torch connection is now compatible with EWM X technology.
- This allows you to connect digital EWM multi-function torches with display and remote-control functions, in addition to conventional welding torches.

SPOTARC WELDING TORCH +

- Pinpoint precision – the solution for spot welding fillet welds, edge welds and flat welds.



ACCESSORIES.

NEEDS-ORIENTED AND VERSATILE.

You can enhance the Picotig 220 puls with a comprehensive range of accessories precisely oriented to your needs. From the practical carrying strap, to the foot-operated remote control, to the dirt filter – you decide what your EWM welding machine can do.



CARRYING STRAP

- For easier transport
- Ideal for use on the go and in case of frequently changing working sites



WELDING TORCH

- With integrated double push-button
- Available in different lengths



RTF-X TIG 19POL 5 M

- The RTF-X TIG is a foot-operated remote control with a 19-pole connection and 5 m cable
- Infinitely adjustable welding current (0 to 100%) depending on the main current preselected on the welding machine




TROLLY 35-1

- Transport cart (two wheels) for moving a power source and a shielding gas cylinder up to 33 l (300 bar)
- Solid, sturdy design



DIRT FILTER

- Reliably protects the machine from impurities in difficult working conditions




TECHNICAL DATA.






220 puls DC

PICOTIG

TIG setting range for welding current	5 A–220 A
MMA setting range for welding current	5 A – 190 A
TIG duty cycle (DC) at 40 °C	220 A/40% 190 A/60% 160 A/100%
MMA duty cycle (DC) at 40 °C	190 A / 35% 155 A / 60% 125 A / 100%
Open circuit voltage	97 V
Mains voltage/Tolerance	1 x 230 V (–40% to +15%)
Rec. generator output	8.4 kVA
cos φ / efficiency	0.99–85%
EMC class	A
Insulation class/Protection classification	H / IP23
Torch connection	5-pole, with X technology
Mains connection lead	3.5 m
Product certification	
Standards	IEC 60974-1, -3 and -10 CL.A
Dimensions (L x W x H) mm	454 x 165 x 321
Dimensions (L x W x H) inch	17.9 x 6.5 x 12.6
Weight in kg	10
Weight in lbs	22

ADDITIONAL PICOTIG MODELS.


In addition to the new Picotig 220 puls, the Picotig series also includes other machines from our selection:

PICOTIG	 200 puls DC MV*	 200 puls AC/DC
Multivolt	230 V	115 V
TIG setting range for welding current	5 A–180 A	5 A–150 A
MMA setting range for welding current	5 A–150 A	5 A–110 A
TIG duty cycle (DC) at 40 °C	200 A/25% 150 A/60% 140 A/100%	150 A/35% 120 A/60% 100 A/100%
MMA duty cycle (DC) at 40 °C	150 A/35% 120 A/60% 100 A/100%	110 A/35% 90 A/60% 80 A/100%
Open circuit voltage	90 V	
Mains voltage/Tolerance	1 x 230 V –40% to +15%	1 x 115 V –25% to +15%
Rec. generator output	8.6 kVA	
cos φ / efficiency	0.99 / 86%	
EMC class	A	
Insulation class/Protection classification	H / IP23	
Torch connection	5-pole	5- or 8-pole
Mains connection lead	3.5 m	
Product certification		
Standards	IEC 60974-1, -3 and -10 CL.A	
Dimensions (L x W x H) mm	428 x 181 x 294	539 x 210 x 415
Dimensions (L x W x H) inch	16.9 x 7.1 x 11.6	21.2 x 8.3 x 16.3
Weight in kg	9.8	16.5
Weight in lbs	21.6	36.4
Notes	*Multivolt	Can be combined with a cooling unit.



WE ARE WELDING

EWM GmbH
Dr. Günter-Henle-Straße 8
56271 Mündersbach, Germany
Germany
Tel: +49 2680 181 0
Fax: +49 2680 181 244
E-mail: info@ewm-group.com



#WEAREWELDING

Follow us



EWM is your partner for the best welding technology. With EWM, you'll weld more efficiently, more reliably and produce higher-quality results. Innovative systems, efficient welding procedures, digital technologies & services and EWM's expert consultation help you carry out your welding tasks with perfection.

053-000214-00001 / 2023-08 / © EWM GmbH



www.ewm-group.com/en/

The contents of this document were researched, checked and edited with care. However, it is still subject to alterations, writing errors and mistakes.